

Appl. No. 10/535,297; Docket No. AT 020067
Amdt. dated January 10, 2007
Response to Amdt. Dated October 25, 2006

Amendments to the Claims

1. (*Currently Amended*) A membrane (20) for an electroacoustic transducer (1), which membrane (20) is designed to be capable of vibration with respect to a membrane axis (5), and which has a first membrane side (20a) and a second membrane side (20b), and which has a middle area (50),

wherein a central cup-shaped depression (52) is present in the region of the membrane axis (5), which depression (52) is bounded by a cup bottom wall (52a) and is open towards the first membrane side (20a),

wherein the membrane (20) has stiffening grooves (54, 55, 56, 57) in its middle area (50) which stiffening grooves (54, 55, 56, 57) extend substantially parallel to radial directions, and

wherein at least two stiffening grooves (55, 56) of said stiffening grooves (54, 55, 56, 57) extend up to the depression (52).

2. (*Currently Amended*) A membrane (20) as claimed in claim 1, wherein all stiffening grooves (54, 55, 56, 57) are open towards the second membrane side (20b).

3. (*Currently Amended*) A membrane (20) as claimed in claim 1, wherein the depression (52) has a connecting channel (53), which connecting channel (53) is open towards the second membrane side (20b) and leads into the two stiffening grooves (55, 56) that extend up to the depression (52).

4. (*Currently Amended*) A membrane (20) as claimed in claim 1, wherein the stiffening grooves (54, 55, 56, 57) are angularly regularly spaced in circumferential direction.

5. (*Currently Amended*) A membrane (20) as claimed in claim 1, wherein the stiffening grooves (54, 55, 56, 57) are arranged in at least two groups of stiffening grooves, such that the stiffening grooves (54, 55, 56) of a first group extend up to the depression (52), and the stiffening grooves (57) of a second group terminate before reaching the depression (52).

Appl. No. 10/535,297; Docket No. AT 020067
Amdt. dated January 10, 2007
Response to Amdt. Dated October 25, 2006

6. (*Currently Amended*) A membrane (20) as claimed in claim 1, wherein the stiffening grooves (54, 55, 56, 57) extend with their ends facing away from the depression (52) up to an annular intermediate portion (22) of the membrane (20).

7. (*Currently Amended*) A membrane (20) as claimed in claim 1, wherein the stiffening grooves (54, 55, 56, 57) extend linearly.

8. (*Currently Amended*) A membrane (20) as claimed in claim 1, wherein the stiffening grooves (54, 55, 56, 57) each have groove side walls (58, 59) which are substantially parallel to one another.

9. (*Currently Amended*) A membrane (20) as claimed in claim 1, wherein the stiffening grooves (54, 55, 56, 57) have a substantially U-shaped cross-section.

10. (*Currently Amended*) A membrane (20) as claimed in claim 1, wherein the connecting channel (53) has a cross-section smaller than the cross-section of the stiffening grooves (54, 55, 56, 57).

11. (*Currently Amended*) An electroacoustic transducer (1) having a membrane (20), wherein the transducer (1) is provided with a membrane (20) as claimed in claim 1.